



Thông số Sạc cho Pin lithium AGV		
Stt	Miêu tả	Thông số
1	Kích thước (L x W x H)	245x162x127 mm
2	Nguồn	24V
3	Dòng	20A
4	Giao tiếp	RS485 / CAN

Tolerance class		Standard dimension range							
Symbol	Description	>0,5 ~ -3 incl	>3-6 incl	>6-30 incl	>30-120 incl	>120-400 incl	>400-1000 incl	>1000-2000 incl	>2000-4000 incl
<input type="checkbox"/>	f	± 0.05	± 0.05	± 0.1	± 0.15	± 0.2	± 0.3	± 0.5	
<input checked="" type="checkbox"/>	m	± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2
<input type="checkbox"/>	c	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2	± 3	± 4
<input type="checkbox"/>	v		± 0.5	± 1	± 1.5	± 2.5	± 4	± 6	± 8

Note: (1) Tolerance for standard dimensions of less than 0.5mm shall be specified individually. JIS B 0405 - 1991-

Revision	Date	Tada Automation Co., Ltd		
Material				
Heat treatment		TITLE		
Surface treatment		Sạc Pin Lithium AGV TD-AGV-FC-24-20		
Drawn by	Lê Thăng	SIZE	DWG NO	REV
Checked by	Hoàng Kiên	A3	TD-AGV-FC-24-20	
Approved by	Nguyễn Trường	SCALE	1:2	SHEET 1 OF 1